

**CLAIMS:**

1. A juvenile vehicle seat comprising a base and a cup holder, the cup holder having a retracted position adjacent the base and an extended position spaced from the base.
2. The juvenile vehicle seat of claim 1, wherein the cup holder is carried by a connecting member, the connecting member being movable relative to the base.
3. The juvenile vehicle seat of claim 1, wherein the cup holder is slidably mounted to the base.
4. The juvenile vehicle seat of claim 2, wherein the base provides a receptor for the connecting member.
5. The juvenile vehicle seat of claim 2 further comprising a detent carried on one of the base or the connecting member and a notch provided in the other of the base or the connecting member to inhibit movement of the cup holder from at least one of the retracted or extended positions.
6. The juvenile vehicle seat of claim 2, wherein the connecting member includes a detent, the base includes a notch, and the detent engages the notch to inhibit movement of the cup holder from the extended position toward the retracted position.
7. The juvenile vehicle seat of claim 6, wherein the base further includes an opening and the detent engages an edge of the opening to inhibit movement of the cup holder from the retracted position toward the extended position.
8. The juvenile vehicle seat of claim 7, wherein the connecting member further includes a catch that engages the edge of the opening to inhibit removal of the cup holder from the base.
9. A juvenile seat assembly comprising:  
a juvenile vehicle seat, and

a cup holder movably secured to the juvenile vehicle seat, the cup holder being positionable between a first position and a second position,

wherein the cup holder is spaced apart from the juvenile vehicle seat by a first distance when the cup holder is in the first position and is spaced apart from the juvenile vehicle seat by a second distance when the cup holder is in the second position, the first distance being less than the second distance.

10. The assembly of claim 9, wherein the cup holder includes a cylindrically-shaped cup retainer defined therein.

11. The assembly of claim 9, wherein the cup holder is slidably secured to the juvenile seat.

12. The assembly of claim 9, wherein the assembly further comprises a base, the seat being removably secured to the base, and the cup holder is movably secured to the base.

13. The assembly of claim 12, wherein the base is formed to include an aperture defined therein, and the cup holder includes a connector, the connector extending into the aperture.

14. The assembly of claim 13, wherein the connector includes a first portion and the base includes a second portion, the first portion cooperating with the second portion to inhibit movement of the cup holder from at least one of the first or second positions.

15. The assembly of claim 14, wherein the first portion includes a detent and the second portion provides an engagement edge, the detent engaging the edge when the cup holder is in the first position to inhibit movement of the cup holder from the first position toward the second position.

16. The assembly of claim 15, wherein the first portion further includes a catch that engages the edge when the cup holder is in the second position to inhibit removal of the cup holder from the base.

17. The assembly of claim 15, wherein the second portion includes a notch and the detent engages the notch when the cup holder is in the second position to inhibit removal of the cup holder from the base and to inhibit movement of the cup holder from the second position toward the first position.

18. A juvenile vehicle seat comprising

2025-03-14 10:03:03

a cup holder coupled to the seat and movable relative to the seat between a retracted position proximate the seat and an extended position spaced apart from the seat,

the cup holder having a connecting member engaging the seat to  
5 inhibit movement of the cup holder from at least one of the retracted and extended positions.

19. The juvenile vehicle seat of claim 18, wherein the connecting member includes a retainer and the seat includes a first retainer engaging portion and a second retainer engaging portion, wherein the retainer engages the first retainer  
10 engaging portion to inhibit movement of the cup holder from the extended position and the retainer engages the second retainer engaging portion to inhibit movement of the cup holder from the retracted position.

20. The juvenile vehicle seat of claim 18, wherein the connecting member includes a first retainer and a second retainer and the seat includes a retainer  
15 engaging portion, wherein the first retainer engages the retainer engaging portion to inhibit movement of the cup holder from the retracted position and the second retainer engages the retainer engaging portion to inhibit movement of the cup holder from the seat.

20

25

30

FOI b7E b7C b7D b7F b7G b7H b7I b7J b7K b7L b7M b7N b7O b7P b7Q b7R b7S b7T b7U b7V b7W b7X b7Y b7Z b8A b8B b8C b8D b8E b8F b8G b8H b8I b8J b8K b8L b8M b8N b8O b8P b8Q b8R b8S b8T b8U b8V b8W b8X b8Y b8Z b9A b9B b9C b9D b9E b9F b9G b9H b9I b9J b9K b9L b9M b9N b9O b9P b9Q b9R b9S b9T b9U b9V b9W b9X b9Y b9Z